# Hand Operated Curtain Track Systems










### Hand Operated Curtain Track System

## Silent Gliss® 6290 Safety Track



#### **Product Information**


- Ceiling fix safety track unique gliders designed to separate from profile when a specific weight is applied (4-6kg)
- Discreet hand drawn curtain track for contract applications ideal for hospitals and schools
- Blue glider supplied for leading edge of curtain designed to separate at a higher weight (8-10kg) as more pressure is applied here when curtains are operated
- Profile is not pre-drilled in order to prevent impairing appearance from the room
- Profile fixed using self drilling screws. No gap between profile and ceiling
- For light to medium weight curtains
- White profile only
- Standard profile lengths available 5m and 6m
- Unique blue and yellow safety gliders for easy identification

Silent Gliss®

3

#### Profile, Bending and Specification Information

#### 6290 Ceiling Fix







#### Specification Guide - download from www.silentgliss.co.uk (password required)

Silent Gliss 6290 hand operated curtain track in white powder coated aluminium. Fix track to ceiling with self drilling wood screws. Special gliders to run in pofile 6148 (10/m) amd 6149 (2/length). Fix with secure endcovers 6122 at either end.

#### Safety System Key Parts


#### Safety Release Function





B: Glider deforms under pressure

C: Release under following pull weights: Glider 6148 (yellow for release between 4-6kg pull); Glider 6149 (blue for release between 8-10kg pull)



6122: Endstop (with end glider 6149 in place)

6021/6290 system can assist in the prevention of self harm in hospitals, schools and psychiatric situations. Please see specific pull out weights on individual gliders. Please also note that the longer the individual track and the more gliders used, the cumulative total pull-out weight when in a stacked position will increase and therefore support more weight.

A risk assessment of the area should always be carried out.

#### Fitting Information

#### Maximum recommended fixing points




Important: when installing system 6290 with the intention of reducing the opportunity of self harm, Silent Gliss recommend the following:

- The first and final fixings must be no more than 1cm from either end of the track.
- If fixing to a baton, ensure the profile does not project past the edge of the baton.
- If fixing to uneven wall surfaces (with or without batons), use a sealant or similar compound around the baton/track to ensure no gaps remain.


#### **Fitting Options**

#### Ceiling fix with 6290 with single profile



The final distance may be outside of the recommendations above depending on curtain heading, make-up and any obstructions.

#### Ceiling fix with two or multiple profiles



The final distance may be outside of the recommendations above depending on curtain heading, make-up and any obstructions.

#### Standard Accessories

6122	Endstop	6148	Safety glider (yellow)	
6149	Safety glider (blue)	6290	Profile	

#### **Optional Accessories**

0688 Wood screw (self drilling)		10430	Draw rod with hook, 50cm	
---------------------------------	--	-------	--------------------------	--



10431	Draw rod with hook, 75cm	10432	Draw rod with hook, 100cm	
10433	Draw rod with hook, 125cm	10434	Draw rod with hook, 150cm	

### Useful Information and Sewing Accessories




Diagram uses safety glider measured to the inside of the glider eye.

3562	Standard tape	3582 Hook	
3599	Hook		



## www.silentgliss.co.uk

Silent Gliss Ltd Pyramid Business Park Poorhole Lane Broadstairs Kent CT10 2PT Great Britain

Tel: 0044 (0) 1843 863571 Fax: 0044 (0) 1843 864503 sales@silentgliss.co.uk